



This conduit is an advanced product that is ideal for all general-purpose applications where durability and high flexibility is required. With an all PVC construction with spiral reinforcement, this conduit offers all-round protection and facilitates fast insertion of the cables (due to its smooth inner bore).

It will not support combustion and is self-extinguishing. It also offers a high ingress protection of IP65 on all fittings.

**Technical Details**

Temperature Range: -15°C to +70°C (Static) , -5°C to +60°C (Moving)  
Material: Thermoplastic resin with polyvinyl chloride (PVC)  
Colour: Black (Light Grey available upon request)  
Flame resistance: Self-extinguishing within 30 seconds (UL94V0)

Ingress Protection: IP65  
Compression Strength: 320N  
Other Information: UV Resistant, CE,  
Manufactured to BS EN 61386 & UL 1696

Product Code	Trade Size	Internal Diameter	External Diameter	Coil Size
TA8-30M	8mm	6.0mm	10.0mm	30m
TA10-30M	10mm	8.0mm	12.4mm	30m
TA12-30M	12mm	10.0mm	14.6mm	30m
TA16-30M	16mm	12.0mm	16.2mm	30m
TA20-30M	20mm	16.0mm	20.2mm	30m
TA25-30M	25mm	22.0mm	26.3mm	30m
TA32-30M	32mm	28.0mm	33.0mm	30m
TA40-30M	40mm	35.0mm	40.2mm	30m
TA50-30M	50mm	40.0mm	45.3mm	30m
TA63-30M	63mm	50.0mm	56.0mm	30m
TA75-30M	75mm	60.0mm	66.4mm	30m

*PVC Spiral Straight Fittings*

- Locknuts included
- 2 Part Fitting (Body & Shell)
- IP65



Product Code	Conduit Size	Thread Size	Pack Size
TAF16	16mm	M16 x 1.5mm	10
TAF20	20mm	M20 x 1.5mm	10
TAF25	25mm	M25 x 1.5mm	10
TAF32	32mm	M32 x 1.5mm	10
TAF40	40mm	M40 x 1.5mm	10
TAF50	50mm	M50 x 1.5mm	10
TAF63	63mm	M63 x 1.5mm	10

*PVC Spiral One Piece Swivel Fittings*

- Locknuts included
- Screw fit design
- IP65



Product Code	Conduit Size	Thread Size	Pack Size
TAF16DS	16mm	M16 x 1.5mm	10
TAF20DS	20mm	M20 x 1.5mm	10
TAF25DS	25mm	M25 x 1.5mm	10