



An highly flexible stainless steel conduit that provides excellent mechanical and chemical protection for cables in applications that require a high degree of corrosion protection but where protection from ingress of water is not required.

Typical applications include the steel, foundry, marine and shipbuilding industries. Stainless steel conduit is also the ideal choice for outer casing for temperature measuring devices and sensitive fibre optics.

Technical Details

Temperature Range: -45°C to +400°C
Material: 304 Stainless Steel Colour: Self-coloured
Ingress Protection: IP40

Compression Strength: 1,250 N
Impact Strength: 6 J
Tensile Strength: 500 N
Other Information: Low Fire Hazard
Manufactured to BS EN 61386

Product Code	Trade Size	Internal Diameter	External Diameter	Coil Size
TSS10	10mm	6.9mm	9.0mm	100m
TSS16	16mm	13.0mm	16.0mm	50m
TSS20	20mm	17.0mm	20.5mm	50m
TSS25	25mm	21.0mm	25.0mm	50m

304 Stainless Steel Fixed Fittings

Material: 304 Stainless Steel
Temperature Range: -45°C to +400°C
Construction: 2 Part Fitting (Body & Shell)
IP Rating: IP40

Product Code	Conduit Size	Thread Size	Pack Size
TSSF16	16mm	M16 x 1.5mm	1
TSSF20	20mm	M20 x 1.5mm	1
TSSF25	25mm	M25 x 1.5mm	1

